

Serial No. 10/072,782
Applicants: Webb et al.
Page 2

In the Claims:

1. (Currently Amended) An apparatus, comprising:
a server ~~adapted~~operating to receive and store at least one request to modify the behavior of an implantable medical device, the request received from a programmer and created by a clinician via the programmer at a first selected time; provided by a programmer adapted to allow a clinician to create the at least one request at a first selected time;
a monitor ~~adapted~~operating to receive the at least one request from the server and transmit the requests to the implantable medical device at a second selected time; and
a bi-directional communications system ~~adapted to~~communicatively coupling couple the server and the monitor.
2. (Currently Amended) The apparatus of claim 1, wherein the server is further ~~adapted to verify~~verifies that the clinician is authorized to submit requests to the implantable medical device.
3. (Currently Amended) The apparatus of claim 2, wherein the bi-directional communication system is ~~adapted to provide~~provides a secure communication link between the server and the monitor.
4. (Currently Amended) The apparatus of claim 1, wherein the monitor is ~~adapted to decrypts~~the requests.
5. (Currently Amended) The apparatus of claim 4, wherein the monitor is ~~adapted to transmits~~the decrypted requests to the implantable medical device using a radio frequency transmitter.

Serial No. 10/072,782
Applicants: Webb et al.
Page 3

6. (Currently Amended) The apparatus of claim 5, wherein the implantable medical device ~~is adapted to receive~~ receives the decrypted requests using a radio frequency receiver.

7. (Original) The apparatus of claim 1, wherein the second selected time is substantially later than the first selected time.

8. (Currently Amended) The apparatus of claim 4, wherein the monitor is ~~adapted to transmit~~ transmits the decrypted requests to a plurality of implantable medical devices.

9. (Currently Amended) The apparatus of claim 8, wherein the server is ~~further adapted to allow~~ allows the clinician to submit requests to at least one of the plurality of implantable medical devices.

10. (Currently Amended) An apparatus, comprising:
a programmer for creating ~~adapted to allow a clinician to create~~, at a first selected time, a plurality of requests to modify the operation of at least one of a plurality of implantable medical devices, wherein a clinician operates the programmer to create the plurality of requests;

B1
a server at a first selected location ~~adapted to~~ operating to receive, store, and encrypt the requests, wherein the server is ~~further adapted to verify~~ verifies that the clinician is authorized to submit requests to the at least one of the plurality of implantable medical devices;

a monitor at a second selected location ~~adapted to~~ operating to receive and decrypt the requests from the server and transmit the requests to the at least one of the plurality of implantable medical device at a second selected time; and

a secure bi-directional communications system ~~adapted to enable~~ enabling the server and the monitor to exchange encrypted information.

Serial No. 10/072,782
Applicants: Webb et al.
Page 4

11. (Original) The apparatus of claim 10, wherein the secure bi-directional communications system comprises a Virtual Private Network.
12. (Original) The apparatus of claim 10, wherein the secure bi-directional communications system comprises a Secure Socket Layer connection.
13. (Currently Amended) The apparatus of claim 10, wherein the monitor comprises a radio frequency transmitter ~~adapted to transmit~~ that transmits the request to the at least one of a plurality of implantable medical devices.
14. (Currently Amended) The apparatus of claim 13, wherein the plurality of implantable medical devices comprise a plurality of radio frequency receivers ~~adapted to~~ that receive requests from the monitor.
15. (Original) The apparatus of claim 10, wherein the second selected time is substantially later than the first selected time.
16. (Original) A method, comprising:
programming at a first selected time at least one request to modify the operation of an implantable medical device;
storing the request at a first selected location;
transmitting the request from the first selected location at a second selected time to a second selected location; and
transmitting the request from the second selected location to the implantable medical device.
17. (Original) The method of claim 16, wherein programming comprises authorizing a clinician to create the at least one request.

Serial No. 10/072,782
Applicants: Webb et al.
Page 5

18. (Original) The method of claim 17, wherein programming further comprises selecting the implantable medical device from among a plurality of implantable medical devices that the clinician is authorized to program.
19. (Original) The method of claim 16, wherein transmitting the request from the first selected location to the second selected location comprises forming a secure communication link between the first selected location and the second selected location.
20. (Original) The method of claim 19, wherein forming a secure connection comprises forming a Virtual Private Network connection.
21. (Original) The method of claim 20, wherein forming a secure connection comprises forming a Secure Socket Layer connection.
22. (Original) The method of claim 19, wherein transmitting the request from the first selected location further comprises encrypting the request at the first location.
23. (Original) The method of claim 22, wherein transmitting the request from the first selected location to the second selected location further comprises transmitting the encrypted request from the first selected location to the second selected location using the secure connection.
24. (Original) The method of claim 23, wherein transmitting the request from the first selected location to the second selected location further comprises decrypting the request at the second selected location.

Serial No. 10/072,782
Applicants: Webb et al.
Page 6

25. (Original) The method of claim 24, wherein transmitting the request from the first selected location to the second selected location comprises retrieving the request at a second selected time that is substantially later than the first selected time.

26. (Currently Amended) A method, comprising:

creating, at a first selected time, at least one request to modify the operation of an implantable medical device using a programmer;

storing the request on a server at a first selected location;

~~encrypting the request on the server at a second selected time in response to notification that a monitor at a second location is substantially ready to receive the request;~~

transmitting the encrypted request from the server to the monitor through a secure bi-directional communications network when a monitor at a second location is substantially ready to receive the request;

decrypting the request on the monitor; and

transmitting the request from the monitor to the implantable medical device using a radio frequency transmitter.

27. (Original) The method of claim 26, wherein creating the request comprises authorizing a clinician to create a request;

28. (Original) The method of claim 26, wherein transmitting the encrypted request from the server to the monitor through a secure bi-directional communications network comprises transmitting the encrypted request through a Virtual Private Network.

Serial No. 10/072,782
Applicants: Webb et al.
Page 7

29. (Original) The method of claim 26, wherein transmitting the encrypted request from the server to the monitor through a secure bi-directional communications network comprises transmitting the encrypted request through a Secure Socket Layer.

30. (Currently Amended) A system, comprising:

a programmer ~~adapted to allow a clinician to create~~ for creating, at a first selected time, a plurality of requests to modify the behavior of at least one of a plurality of implantable medical devices ~~adapted to that~~ deliver therapies to at least one of a plurality of patients, wherein a clinician utilizes the programmer to create the requests;

a secure bi-directional communication network;

a server coupled to the bi-directional communication network at a first location and ~~adapted to that~~ receives, stores, and encrypts the requests, wherein the server is also ~~adapted to verify~~ that the clinician is authorized to submit requests to the at least one of the plurality of implantable medical devices; and

a plurality of monitors coupled to the bi-directional communication network at a plurality of second selected locations and ~~adapted to receive and decrypt~~ the requests from the server and transmit, at a plurality of second selected times, the requests to the at least one of the plurality of implantable medical devices.

31. (Original) The system of claim 30, wherein the bi-directional communications network comprises at least one of a telephone line, an intranet, an internet, a satellite, and a global positioning system.

B1
32. (Original) The system of claim 30, wherein at least one of the plurality of second selected times is substantially later than the first selected time.